



APPROXIMATE QUANTITIES - 10' BARRIER

	PRECAST
CONCRETE CY.	1.16
WWR LB.	30.5
WEIGHT	4650 LBS, 2.3 TONS
FREIGHT	100LF, 10 PCS/TRUCK

WELDED WIRE REINFORCEMENT (WWR)

GENERAL NOTES.

1. DEFORMED WELDED WIRE REINFORCEMENT (WWR) SHALL CONFORM TO ASTM A497.
2. ALL REINFORCEMENT SHALL COMPLY WITH ITEM 440, "REINFORCING STEEL."

GENERAL NOTES

1. CONCRETE SHALL BE CLASS H, WITH A MINIMUM COMPRESSIVE STRENGTH OF 3,600 PSI.
2. JJ-HOOK IS A PROPRIETARY CONNECTION SYSTEM DEVELOPED BY EASI-SET WORLD WIDE AND LICENSED TO SUMMIT PRECAST CONCRETE, LP.

PREPARED FOR:



SUMMIT PRECAST CONCRETE, LP
 15349 SUMMIT PARK DR.
 SUITE 101
 MONTGOMERY, TX 77356
 www.summitprecastconcrete.com
 936-701-1977

REV. NO.	DATE	REVISION

PREPARED BY:



DATE: 07/05/24	SHEET TITLE: PLAN AND ELEVATIONS	DRWN BY: ADVS
SCALE: N.T.S.		CRD BY: DV
PROJECT: CONCRETE SAFETY BARRIER 10'-CSB-F-SHAPE-JJ-HOOK CONNECTION		
SUMMIT PROJECT NO.:	DWG. I.D.	
DELTA PROJ. NO.: 2024.751.003	SHT. NO. 1 OF 1	